



## Acousti-Mat® Perimeter Isolation Strips

Maxxon® Corporation  
 920 Hamel Road, PO Box 253  
 Hamel, MN 55340

Product Safety: 1-800-356-7887  
 Issue date:  
 Revision date: June 2014

### DESCRIPTION

Acousti-Mat Perimeter Isolation Strips are polyethylene isolation material for use with all Sound Mats. The product is extremely flexible and light, making it easy to install and handle. The Acousti-Mat Perimeter Isolation Strip is packaged on a roll for long placement runs and limited cutting.

### RECOMMENDED APPLICATIONS

All applications of Maxxon's Sound Control Matting

#### SPECIFICATIONS

	1"	1.25"	1.5"	2.5"	3"	4" With Tape	5"	2.5" Self Adhesive Isolation Strips	2.5" Isolation Strips	3" Isolation Strips
<b>Thickness</b>	1/8 inch (3 mm)	1/8 inch (3 mm)	1/8 inch (3 mm)	1/8 inch (3 mm)	1/4 inch (6 mm)	1/8 inch (3 mm)	1/8 inch (3 mm)	1/8 inch (3 mm)	1/8 inch (3 mm)	1/4 inch (6 mm)
<b>Roll Width</b>	1 inch (25 mm)	1.25 inches (32 mm)	1.5 inches (38 mm)	2.5 inches (64 mm)	3 inches (76 mm)	4 inches (102 mm)	5 inches (127 mm)	2.5 inches (64 mm)	2.5 inches (64 mm)	3 inches (76 mm)
<b>Length</b>	110 feet (33.5 m)	110 feet (33.5 m)	110 feet (33.5 m)	110 feet (33.5 m)	125 feet (38.1 m)	108 feet (32.9 m)	125 feet (38.1 m)	110 feet (33.5 m)	110 feet (33.5 m)	250 feet (76.2 m)
<b>Roll Diameter</b>	14 inches (356 mm)	14 inches (356 mm)	14 inches (356 mm)	14.5 inches (369 mm)	22.75 inches (578 mm)		14.75 inches (375 mm)	14 inches (356 mm)	14 inches (356 mm)	24 inches (610 mm)
<b>Gross Box Weight</b>	1.75 lbs (.79 kg)	1.5 lbs (.68 kg)	1 lb (.45 kg)	2.8 lbs (1.27 kg)	6.5 lbs (2.95 kg)		2.7 lbs (1.22 kg)	6.8 lbs (3.08 kg)	2.9 lbs (1.32 kg)	1.7 lbs (.77 kg)
<b>Color</b>	White	White	White	White	White	White	White	White	White	White
<b>Box</b>	Contains 12 rolls	Contains 9 rolls	Contains 8 rolls	Contains 8 rolls	Contains 8 rolls	Contains 5 rolls	Contains 4 rolls	Contains 8 rolls	Contains 8 rolls	Contains 1 roll
<b>Part No.</b>	54050	54051	54052	54053	54054	54045	54055	54042	54041	54031
<b>Ships from</b>	Minneapolis MN	Minneapolis MN	Minneapolis MN	Minneapolis MN	Minneapolis MN	Minneapolis MN	Minneapolis MN	Asheville NC	Asheville NC	Asheville NC

### INSTALLATION PROCEDURE

Install Acousti-Mat Perimeter Isolation Strip at the perimeter of all areas receiving Acousti-Mat (including doorframes) and around any protrusions through the installation. This procedure isolates the sound mat floor system from the walls in order to create an acoustical break that will minimize the transmission of sound laterally from the "floating floor" to the walls.

Adhere the foam perimeter isolation strip to the wall or staple as close as possible to the top of the foam strip, above the height of the poured floor.