



## Acousti-Mat® Perimeter Isolation Strips

Maxxon® Corporation  
920 Hamel Road, PO Box 253  
Hamel, MN 55340

Product Safety: 1-800-356-7887  
Issue date:  
Revision date:

### DESCRIPTION

Acousti-Mat Perimeter Isolation Strips are polyethylene isolation material for use with Acousti-Mat LP, Acousti-Mat II, Acousti-Mat 3 and Enkasonic. The product is extremely flexible and light, making it easy to install and handle. The Acousti-Mat Perimeter Isolation Strip is packaged on a roll for long placement runs and limited cutting.

### RECOMMENDED APPLICATIONS

All applications of Maxxon’s Sound Control Matting

#### SPECIFICATIONS

	Self Adhesive Perimeter Isolation Strip	Perimeter Isolation Strip	3" Enkasonic Perimeter Isolation Strip	5" Acousti-Mat Perimeter Isolation Strip
<b>Thickness</b>	1/8 inch (3mm)	1/8 inch (3mm)	1/4 inch (6mm)	1/4 inch (6mm)
<b>Roll Width</b>	2 1/2 inches (63mm)	2 1/2 inches (63mm)	3 inches (76mm)	5 inches (127mm)
<b>Length</b>	110 feet (33.5 m)	110 feet (33.5 m)	250 feet (76m)	250 feet (76m)
<b>Roll Diameter</b>	14 inches (35mm)	14 inches (35mm)	24 inches (60mm)	24 inches (60mm)
<b>Gross Roll Weight</b>	0.5 lb (0.2 kg)	0.5 lb (0.2 kg)	2.0 lb (0.9 kg)	3.5 lb (1.6 kg)
<b>Color</b>	White	White	White	White
<b>Box</b>	Contains 8 rolls	Contains 8 rolls	Contains 1 roll	Contains 1 roll
<b>Part No.</b>	54042	54041	54031	54043

### INSTALLATION PROCEDURE

Install Acousti-Mat Perimeter Isolation Strip at the perimeter of the entire subfloor (including doorframes) and around any protrusions through the installation. This procedure isolates the sound mat floor system from the walls in order to create an acoustical break that will minimize the transmission of sound laterally from the “floating floor” to the walls.

Adhere the foam perimeter isolation strip to the wall or staple as close as possible to the top of the foam strip, above the height of the poured floor.