

Safety Data Sheet according to OSHA-GHS (29 CFR part 1910.1200 HCS 2012)

PRODUCT NAME Maxxon® Underlayments
Product Code: 10006, 10051, 10054, 10058, 10059, 12051, 12054, 12056, 12058, 14051, 14056, 14058, 15051, 15056, 15058, 18051, 18054, 18056, 18058, 18059
Date of Issue: February 2017 Supersedes: May 2015

1. PRODUCT AND COMPANY IDENTIFICATION

Product Identifier: Maxxon® Underlayments
Trade Name: Gyp-Crete®
 Gyp-Crete 2000®/3.2K
 Dura-Cap®
 Therma-Floor®
 Commercial Topping®

Recommended uses: Floor underlayment
Restrictions on uses: Workers should be informed of the potential presence of respirable dust and respirable Crystalline Silica as well as their potential hazards. Appropriate training in the proper use and handling of this material should be provided as required under applicable regulations.

Supplier: Maxxon Corporation
 920 Hamel Road | PO Box 253
 Hamel, MN 55340

Company Telephone/Fax: (763) 478-9600 / (763) 478-2431
Emergency Telephone Number: (800) 424-9300 (CHEMTREC)

2. HAZARDS IDENTIFICATION

Physical Hazards: Not classified
Health Hazards:
 Acute toxicity, oral Category 4
 Serious eye damage Category 1
 Sensitization, skin Category 1
 Carcinogenicity Category 1A
 Specific target organ toxicity, repeated Category 1 (lung)
Environmental Hazards: Not classified
OSHA defined Hazards: Not classified
GHS Label Elements:
Hazard Pictograms



Signal Word: Danger



Safety Data Sheet according to OSHA-GHS (29 CFR part 1910.1200 HCS 2012)

PRODUCT NAME Maxxon® Underlayments
Product Code: 10006, 10051, 10054, 10058, 10059, 12051, 12054,
12056, 12058, 14051, 14056, 14058, 15051, 15056,
15058, 18051, 18054, 18056, 18058, 18059
Date of Issue: February 2017 Supersedes: May 2015

2. HAZARDS IDENTIFICATION (CONTINUED)

Hazard Statement

Harmful if swallowed. Causes serious eye damage. Causes skin irritation. May cause an allergic skin reaction. May cause cancer. Causes damage to organs (lung) through prolonged or repeated exposure.

Precautionary statement

Prevention: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breath dust. Contaminated work clothing must not be allowed out of the workplace. Wash thoroughly after handling. Do not eat, drink, or smoke when using this product. After mixing with water, do not allow prolonged contact with skin until the product has completely hardened and cooled.

Response: If swallowed: Rinse mouth. Call a poison center/doctor if you feel unwell. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center/doctor. If on skin: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse. For specific treatment see Section 4 on the SDS.

Storage: Store away from incompatible materials (see Section 10 of SDS). Protect from moisture. Keep container tightly closed.

Disposal: Dispose of contents/container in accordance with applicable regulations.

Hazard(s) not otherwise classified (HNOC): Heat develops as product hardens. May cause serious burns during hardening (rehydration) resulting in possible permanent injury.

Supplemental information: None

3. COMPOSITION/INFORMATION ON INGREDIENTS

<u>Components</u>	<u>CAS#</u>	<u>Percent</u>
Gypsum (Calcium Sulfate)	10101-41-4	80-90
Portland Cement	65997-15-1	5-10
Crystalline Silica (Quartz)	14808-60-7	1-5
*Other components below reportable levels		3-5

**The specific chemical identity and/or percentage has been withheld as a trade secret.

Composition comments:

Gypsum (Calcium Sulfate) and Portland Cement contain naturally occurring Crystalline Silica (Quartz) which is listed as a possible lung carcinogen. See Section 8 for exposure information.

4. FIRST AID MEASURES

Inhalation: Remove to fresh air. If symptoms persist, get medical attention.

Skin Contact: Remove all contaminated clothing immediately, and wash immediately with soap and water. In case of Eczema or other skin disorders, seek medical attention and take along this SDS instructions.



Safety Data Sheet according to OSHA-GHS (29 CFR part 1910.1200 HCS 2012)

PRODUCT NAME Maxxon® Underlayments
Product Code: 10006, 10051, 10054, 10058, 10059, 12051, 12054,
12056, 12058, 14051, 14056, 14058, 15051, 15056,
15058, 18051, 18054, 18056, 18058, 18059
Date of Issue: February 2017 Supersedes: May 2015

4. FIRST AID MEASURES (CONTINUED)

Eye Contact: Do not rub eyes. Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention immediately.

Ingestion: Rinse mouth. Do not induce vomiting without advice from poison control center. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. May result in obstruction and irritation if ingested. Get medical attention.

Most important symptoms and effects, both acute and delayed: Causes serious eye damage. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. Dust may irritate the respiratory tract, skin and eyes. Skin contact during hardening (rehydration) may slowly develop sufficient heat that may cause severe burns possibly resulting in permanent injury. Do not allow product to harden around any body part or allow continuous, prolonged contact with skin. Handling can cause dry skin. May cause an allergic skin reaction, Dermatitis, rash, coughing, discomfort in the chest, shortness of breath. Prolonged exposure may cause chronic effects.

Indication of any immediate medical attention and special treatment needed: Provide general supportive measures and treat symptomatically. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

General information: IF exposed and concerned: get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this Safety Data Sheet to the doctor in attendance. Wash contaminated clothing before reuse.

5. FIRE FIGHTING MEASURES

Suitable extinguishing media: Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing media: None known.

Specific hazards arising from the chemical: During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters: Self-contained breathing apparatus, and full protective clothing must be worn in case of fire.

Fire-fighting equipment/instructions: Firefighters should wear full protective clothing including self-contained breathing apparatus. Use water spray to cool unopened containers.

Specific Methods: Use standard firefighting procedures, and consider the hazards of other involved materials.

General fire hazards: No unusual fire or explosion hazards noted.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures: Keep unnecessary personnel away. Keep people away from, and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not breath dust. Use a NIOSH/MSHA approved respirator if there is a risk of exposure to dust/fumes at levels exceeding the exposure limits. Do not touch damaged



Safety Data Sheet according to OSHA-GHS (29 CFR part 1910.1200 HCS 2012)

PRODUCT NAME Maxxon® Underlayments
Product Code: 10006, 10051, 10054, 10058, 10059, 12051, 12054, 12056, 12058, 14051, 14056, 14058, 15051, 15056, 15058, 18051, 18054, 18056, 18058, 18059
Date of Issue: February 2017 Supersedes: May 2015

6. ACCIDENTAL RELEASE MEASURES (CONTINUED)

containers or spilled material unless wearing appropriate personal protective equipment. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see Section 8 of the SDS.
Methods and materials for containment and cleaning up: Sweep up or gather material and place in appropriate container for disposal. Minimize dust generation and accumulation. If sweeping of a contaminated area is necessary use a dust suppressant agent which does not react with the product. Contain the spill, then place in a suitable container. For waste disposal, see Section 13 of the SDS. Prevent entry into waterways, sewer, basements or confined areas.
Environmental precautions: Avoid discharge into drains, water courses or onto the ground.

7. HANDLING AND STORAGE

Precautions for Safe Handling: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Minimize dust generation and accumulation. Provide appropriate exhaust ventilation at places where dust is formed. Do not breathe dust. Do not taste or swallow. Avoid contact with eyes, skin and clothing. Avoid prolonged exposure. When using, do not eat, drink or smoke. Should be handled in closed systems, if possible. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices.
Conditions for safe storage, including any incompatibilities: Store in a dry place. Store in original tightly closed container. Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS). Keep away from food, drink and animal feeding stuffs.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Occupational exposure limits
US OSHA Table Z-1: Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value	Form
Calcium Sulfate, Dihydrate (CAS 10101-41-4)	PEL	5 mg/m ³	Respirable fraction
		15 mg/m ³	Total dust
Crystalline Silica (Quartz) (CAS 14808-60-7)	PEL	.05 mg/m ³	
Portland Cement (CAS 65997-15-1)	PEL	5 mg/m ³	Respirable fraction
		15 mg/m ³	Total dust



Safety Data Sheet according to OSHA-GHS (29 CFR part 1910.1200 HCS 2012)

PRODUCT NAME Maxxon® Underlayments
Product Code: 10006, 10051, 10054, 10058, 10059, 12051, 12054, 12056, 12058, 14051, 14056, 14058, 15051, 15056, 15058, 18051, 18054, 18056, 18058, 18059
Date of Issue: February 2017 Supersedes: May 2015

8. EXPOSURE CONTROLS/PERSONAL PROTECTION (CONTINUED)

US ACGIH Threshold Limit Values: Time Weighted Average (TWA): mg/m³, non-standard units

Components	Type	Value	Form
Calcium Sulfate, Dihydrate (CAS 10101-41-4)	TWA	10 mg/m ³	Inhalable fraction
Crystalline Silica (Quartz)* (CAS 14808-60-7)	TWA	0.025 mg/m ³	Respirable fraction
Portland Cement (CAS 65997-15-1)	TWA	1 mg/m ³	Respirable fraction

US NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value	Form
Calcium Sulfate, Dihydrate (CAS 10101-41-4)	TWA	5 mg/m ³	Respirable
		10 mg/m ³	Total
Crystalline Silica (Quartz)* (CAS 14808-60-7)	TWA	0.05 mg/m ³	Respirable dust
Portland Cement (CAS 65997-15-1)	TWA	5 mg/m ³	Respirable
		10 mg/m ³	Total

Biological limit values: No biological exposure limits noted for the ingredient(s).

Exposure Guidelines: Occupational exposure to nuisance dust (total and respirable) and respirable Crystalline Silica should be monitored and controlled.

Appropriate engineering controls: When using product, provide local and general exhaust ventilation to keep airborne dust concentrations below exposure limits. Use wet methods, if appropriate, to reduce the generation of dust.

Individual protection measures, such as personal protective equipment

Eye/Face protection: Wear safety glasses with side shields (or goggles). Ensure compliance with OSHA's PPE standard (29 CFR 1910.132 and .133) for eye and face protection. Safety shower/eye wash fountain must be readily available in the workplace area (29 CFR 1910.151(c)).

Skin protection

Hand protection: Wear appropriate chemical resistant gloves.

Other: Impervious protective clothing and gloves recommended to prevent drying or irritation of skin. Ensure compliance with OSHA's PPE standards (29 CFR 1910.132 (general) and 138 (hand protection)). Safety shower/eye wash fountain is recommended in the workplace area (29 CFR 1910.151(c)).

Respiratory protection: A NIOSH approved dust mask or filtering face piece is recommended in poorly ventilated areas or when permissible exposure limits may be exceeded. Respirators



Safety Data Sheet according to OSHA-GHS (29 CFR part 1910.1200 HCS 2012)

PRODUCT NAME Maxxon® Underlayments
Product Code: 10006, 10051, 10054, 10058, 10059, 12051, 12054,
12056, 12058, 14051, 14056, 14058, 15051, 15056,
15058, 18051, 18054, 18056, 18058, 18059
Date of Issue: February 2017 Supersedes: May 2015

8. EXPOSURE CONTROLS/PERSONAL PROTECTION (CONTINUED)

should be selected by and used under the direction of a trained health and safety professional following requirements found in OSHA's respirator standard (29 CFR 1910.134) and ANSI's standard for respiratory protection (Z88.2).

Thermal hazards: Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations: Observe any medical surveillance requirements. Keep away from food and drink. Always observe good personal hygiene measures such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Appearance Powder
Physical state: Solid
Form: Powder
Color: Grey
Odor: Odorless
Odor Threshold: Not Available
pH value: 10 - 12
Melting point / freezing point: 2642°F (1450°C) estimated
Initial Boiling point and boiling range: Not Available
Flash point: Not Applicable
Evaporation rate: Not Available
Flammability (solid, gas): Not Available
Flammability limit - lower %: Not Applicable
Flammability limit - upper %: Not Applicable
Explosive limit - lower %: Not Applicable
Explosive limit - upper %: Not Applicable
Vapor pressure: Not Applicable
Vapor density: Not Applicable
Relative density: 2.26 - 2.3 g/cm³ estimated
Solubility(ies), (water): Insoluble
Partition coefficient (n-octanol / water): Not Available
Auto Ignition Temperature (AIT): Not Available
Decomposition Temperature: Not Available
Viscosity: Not Available
Other information:
Exploding Properties: Not Explosive
Oxidizing Properties: Not Oxidizing
Specific Gravity: 2.26 - 2.3



Safety Data Sheet according to OSHA-GHS (29 CFR part 1910.1200 HCS 2012)

PRODUCT NAME Maxxon® Underlayments
Product Code: 10006, 10051, 10054, 10058, 10059, 12051, 12054,
12056, 12058, 14051, 14056, 14058, 15051, 15056,
15058, 18051, 18054, 18056, 18058, 18059
Date of Issue: February 2017 **Supersedes:** May 2015

10. STABILITY AND REACTIVITY

Reactivity: Reacts with water (normal condition of use).

Chemical stability: Stable under normal conditions.

Possibility of hazardous reactions: Not expected under conditions of normal use.

Conditions to avoid: Contact with incompatible materials. Avoid dispersal of dust in the air (i.e. clearing dust surfaces with compressed air). Exposure to moisture.

Incompatible materials: Acids.

Hazardous decomposition products: May include, and are not limited to: Calcium Oxide, Sulfur Dioxide.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation: May cause damage to organs through prolonged or repeated exposure by inhalation. Dust may irritate respiratory system.

Skin contact: Dust or powder may irritate the skin. May cause an allergic skin reaction. Skin contact during hardening (rehydration) may slowly develop sufficient heat that may cause severe burns possibly resulting in permanent injury. Do not allow product to harden around any body part or allow continuous, prolonged contact with the skin. Handling can cause dry skin.

Eye Contact: Causes serious eye damage.

Ingestion: Harmful if swallowed.

Symptoms related to the physical, chemical and toxicological characteristics: Causes serious eye damage. Dusts may irritate the respiratory tract, skin and eyes. Coughing. Discomfort in the chest. Shortness of breath. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin contact during hardening (rehydration) may slowly develop sufficient heat that may cause severe burns possibly resulting in permanent injury. Do not allow product to harden around any body part or allow continuous, prolonged contact with skin. Handling can cause dry skin. May cause an allergic skin reaction, Dermatitis, rash.

Information on toxicological effects

Acute toxicity: Harmful if swallowed.

Product	Species	Test Results
Maxxon Underlayments		
Acute		
<i>Inhalation</i>		
LC50	Rat	828 mg/L, 4 hours estimated
<i>Oral</i>		
LD50	Rat	1786 mg/kg estimated
Product	Species	Test Results
Calcium Sulfate, Dihydrate (CAS 10101-41-4)		
Acute		
<i>Oral</i>		
LD50	Rat	>1,581 mg/kg

*Estimates for product may be based on additional component data not shown.



Safety Data Sheet according to OSHA-GHS (29 CFR part 1910.1200 HCS 2012)

PRODUCT NAME Maxxon® Underlayments
Product Code: 10006, 10051, 10054, 10058, 10059, 12051, 12054, 12056, 12058, 14051, 14056, 14058, 15051, 15056, 15058, 18051, 18054, 18056, 18058, 18059
Date of Issue: February 2017 Supersedes: May 2015

11. TOXICOLOGICAL INFORMATION (CONTINUED)

Skin corrosion/irritation: Skin contact during hardening (rehydration) may slowly develop sufficient heat that may cause severe burns possibly resulting in permanent injury. Do not allow product to harden around any body part or allow continuous, prolonged contact with skin. Handling can cause dry skin.

Serious eye damage/eye irritation: Causes serious eye damage.

Respiratory or skin sensitization

Respiratory sensitization: Not classified

Skin sensitization: May cause an allergic skin reaction.

Germ cell mutagenicity: Not classified

Carcinogenicity: Exposure to respirable Crystalline Silica in the form of Quartz or Cristobalite from occupational sources is listed by IARC and NTP as a lung carcinogen. Prolonged exposure to a respirable Crystalline Silica has been known to cause Silicosis, a lung disease, which may be disabling. While there may be a factor of individual susceptibility to a given exposure to a respirable Silica dust, the risk of contracting Silicosis and the severity of the disease is clearly related to the amount of respirable Crystalline Silica exposure and the length of time (usually years) of exposure.

IARC Monographs, Overall Evaluation of Carcinogenicity

Crystalline Silica (Quartz)* (CAS 14808-60-7)

1 - Carcinogenic to humans

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed

Reproductive toxicity: Not classified

Specific target organ toxicity - single exposure: Not classified

Specific target organ toxicity - repeated exposure: Causes damage to organs (lung) through prolonged or repeated exposure.

Aspiration hazard: Not an aspiration hazard.

Chronic effects: Causes damage to organs through prolonged or repeated exposure. Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.

12. ECOLOGICAL INFORMATION

Ecotoxicity: The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment. Large quantities of this product may be harmful to aquatic life due to high pH.

Components	Species	Test Results
Calcium Sulfate, Dihydrate (CAS 10101-41-4)		
Aquatic		
<i>Acute</i>		
Fish	LC50 Fathead minnow (Pimephales promelas)	> 1,970 mg/L, 96 hours



Safety Data Sheet according to OSHA-GHS (29 CFR part 1910.1200 HCS 2012)

PRODUCT NAME Maxxon® Underlayments
Product Code: 10006, 10051, 10054, 10058, 10059, 12051, 12054,
12056, 12058, 14051, 14056, 14058, 15051, 15056,
15058, 18051, 18054, 18056, 18058, 18059
Date of Issue: February 2017 Supersedes: May 2015

12. ECOLOGICAL INFORMATION (CONTINUED)

Components	Species	Test Results
Crystalline Silica (Quartz)* (CAS 14808-60-7)		
Aquatic		
<i>Acute</i>		
Fish	LC50 Zebra Danio (Danio Rerio)	> 10,000 mg/L, 96 hours OECD SIDS

*Estimates for product may be based on additional component data not shown.

Persistence and degradability: No data is available on the degradability of this product.

Bioaccumulative potential: No data is available.

Mobility in soil: No data is available.

Other adverse effects: No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. DISPOSAL CONSIDERATIONS

Disposal instructions: Under RCRA, it is the responsibility of the user of the product to determine, at the time of disposal, whether the product meets RCRA criteria for hazardous waste.

Local disposal regulations: Dispose in accordance with all applicable regulations.

Hazardous waste code: The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

Waste from residues/unused products: Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

Contaminated packaging: Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. TRANSPORTATION INFORMATION

DOT: Not regulated as dangerous goods.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code: Not applicable.

15. REGULATORY INFORMATION

US Federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated

**Safety Data Sheet according to OSHA-GHS
(29 CFR part 1910.1200 HCS 2012)**

PRODUCT NAME Maxxon® Underlayments
Product Code: 10006, 10051, 10054, 10058, 10059, 12051, 12054,
12056, 12058, 14051, 14056, 14058, 15051, 15056,
15058, 18051, 18054, 18056, 18058, 18059
Date of Issue: February 2017 Supersedes: May 2015

15. REGULATORY INFORMATION (CONTINUED)

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed

SARA 304 Emergency release notification

Not regulated

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard Categories Immediate Hazard - Yes
Delayed Hazard - Yes
Fire Hazard - No
Pressure Hazard - No
Reactivity Hazard - No

SARA 302 Extremely hazardous substance: Not Listed

SARA 311/312 Hazardous Chemical: Yes

SARA 313 (TRI reporting): Not regulated

Other federal regulations

Clean Air ACT (CAA) Section 112 Hazardous Air Pollutants (HAPs) List
Not regulated

Clean Air ACT (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)
Not regulated

SAFE Drinking Water Act (SDWA): Not regulated

US State Regulations

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

Crystalline Silica (Quartz) (CAS 14808-60-7)



US. California Proposition 65

WARNING: This product can expose you to chemicals including Crystalline Silica (Quartz), which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

Crystalline Silica (Quartz) (CAS 14808-60-7) Listed: October 1, 1988



Safety Data Sheet according to OSHA-GHS (29 CFR part 1910.1200 HCS 2012)

PRODUCT NAME Maxxon® Underlayments
Product Code: 10006, 10051, 10054, 10058, 10059, 12051, 12054,
 12056, 12058, 14051, 14056, 14058, 15051, 15056,
 15058, 18051, 18054, 18056, 18058, 18059
Date of Issue: February 2017 Supersedes: May 2015

15. REGULATORY INFORMATION (CONTINUED)

International Inventories		
Country(s) or region	Inventory Name	On inventory (yes/no)*
Canada	Domestic Substances List (DSL)	Yes
US & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s). A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

Product List: Gyp-Crete®
 Gyp-Crete 2000®/3.2K
 Gyp-Crete® Floor Underlayment LC
 Therma-Floor®
 Dura-Cap®
 Commercial Topping®

Issue Date: May 2015
Version #: 03
Revision Date: January 26, 2017
Prepared by: Maxxon Corporation

HMIS® ratings: Health: 3
 Flammability: 0
 Physical hazard: 1

NFPA ratings: Health: 3
 Flammability: 0
 Instability: 0

0=Minimal 1=Slight 2=Moderate 3=Serious 4=Severe *=Chronic

Disclaimer:
 This SDS is intended to quickly provide useful information to the user(s) of this material or product. It is not intended to serve as a comprehensive discussion of all possible risks or hazards, and it assumes a reasonable use of the product. The information contained in this SDS is believed to be accurate as the date of preparation of this SDS and has been compiled from sources believed to be reliable. It is offered for your consideration, investigation and verification. The user or handler (or their employer) should consider the specific conditions in which this material will be used, handled or stored and determine what



Safety Data Sheet according to OSHA-GHS (29 CFR part 1910.1200 HCS 2012)

PRODUCT NAME Maxxon® Underlayments
Product Code: 10006, 10051, 10054, 10058, 10059, 12051, 12054,
12056, 12058, 14051, 14056, 14058, 15051, 15056,
15058, 18051, 18054, 18056, 18058, 18059
Date of Issue: February 2017 Supersedes: May 2015

16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION (CONT)

specific safety or other precautions are required. Employers should ensure that their employees, agents, contractors and customers who will use the product receive adequate warnings and safe handling procedures, including a current SDS. Product users or handlers (or their employer) who are unsure of what specific precautions are required should consult their employer, product supplier, or safety or health professionals before handling or working with this product. Please notify us immediately if you believe this SDS or other safety and health information about this product is inaccurate or incomplete.

Revision Information:

This document has undergone significant changes and should be reviewed in its entirety.